## CHEVROLET EL CHIMINATION







New El Camino presents the crisp, sculptured lines of 1959 Chevrolet passenger car styling, whether viewed from the rear, front or side.



El Camino interior is done in high fashion with bright, beautiful vinyl seat upholstery and new passenger car instrument panel.





IT'S MAGNIFICO!


Chevrolet brings you the brightest new idea of the year!

> El Camino dash and decor will do you and your business proud . . . and with premium features such as these, this new beauty knows how to work!






STURDY X-BUILT SAFETY-GIRDER FRAME. All-welded box section side members and box girder center beam give rigidity that resists strains from maximum loads and rutty roads. Tough frame is a solid reason for high 4,900-lb. maximum G.V.W. rating.



POSITRACTION REAR AXLE! This extra-cost option enables the El Camino to handle on or off-the-road hauls with ease. Positraction directs the power to whichever wheel is getting the best traction. It helps wheels to grip on any road surface for safer control.



**EFFICIENT HI-THRIFT 6!** Fewer stops for fuel, lower driving costs, stem from new Hi-Thrift 6 advancements. New camshaft design, for instance, can improve gas econ-omy by as much as 10% and it gives the engine greater torque (more pulling power). Hi-Thrift 6 is rated at 135 horsepower.



MODERN SHORT-STROKE V8 POWER. Two up-to-the-minute V8's complement the advanced styling of the El Camino. Fast-stepping, economical performance is provided by either the smooth 185-h.p., 283-cubic-inch Turbo-Fire V8 . . or the mighty 230-h.p. Super Turbo-Fire V8\*.




GLAMOR THAT KNOWS HOW TO WORK HARD. El Camino takes big cargoes; the pickup box is 76¼" long, 64¼" wide, and 12¾" deep! Side panels are double-walled to protect the smooth exterior appearance. Graintight tailgate is constructed to last, and so is the durable, steel-ribbed body floor.

\*Optional at extra cost.

## **SPECIFICATIONS**

AXLE, FRONT: Independent suspension; capacity 2450 lb. AXLE. REAR: Ratio 3.55; capacity 3000 lb. BRAKES, SERVICE: Front 11" x 24"; rear 11" x 27"; lining area 199 sq. in. BUMPERS: Front and rear. CLUTCH: (1180) dia. 9½"; (1280) dia. 10". DIRECTIONAL SIGNALS: Front and rear. ENGINE: (1180) Hi-Thrift 6; (1280) Iurbo-Fire V8. FRAME: Safety-Girder. FUEL TANK: Capacity 17 gallons. GENERATOR: 12-Volt, 30-amp. LIGHTS: Head, parking, dual tail and stop; directional signals. MIRROR, REARVIEW: Interior. SHOCK ABSORBERS: Froot and Rear. SPRINGS, FRONT: Coil; capacity 1030 lb. ea. at ground. SPRINGS, REAR: Coil, capacity 1315 b. ea. at ground. STEERING: Ball-gear; ratio 28.0; wheel dia. 17". TIRES: Five tubeless 8.00-14/4PR front, single rear, spare. TRANSMISSION: 3-speed Synchro-Mesh. WHEELS: Five 14" x 5J; spare carrier inside cab. WINDSHIELD WIPERS: Dual electric; single-speed.

All illustrations and specifications contained in this literature are based on the latest product information available at the time of publication approval. The right is reserved to make changes at any time without notice in prices, colors, materials, equipment, specifications and models, and also to discontinue models. CHEVROLET MOTOR DIVISION, GENERAL MOTORS CORPORATION, DETROIT 2, MICH.



IT'S MAGNIFICO!

EL CAMINO!

Chevrolet brings you the brightest new idea of the year!

> do you and your business proud . . . and with premium features such as these, this new beauty knows how to work!






STURDY X-BUILT SAFETY-GIRDER FRAME. All-welded box section side members and box girder center beam give rigidity that resists strains from maximum loads and rutty roads. Tough frame is a solid reason for high 4,900-lb. maximum G.V.W. rating.



POSITRACTION REAR AXLE! This Camino to handle on or off-theroad hauls with ease. Positraction directs the power to whichever wheel is getting the best traction. It helps wheels to grip on any road surface for safer control.



for fuel, lower driving costs, stem from new Hi-Thrift 6 advance-ments. New camshaft design, for instance, can improve gas econ-omy by as much as 10% and it gives the engine greater torque (more pulling power). Hi-Thrift 6 is rated at 135 horsepower.



MODERN SHORT-STROKE V8 of the El Camino. Fast-stepping, economical performance is provided by either the smooth 185-h.p., 283-cubic-inch Turbo-Fire V8... or the mighty 230-h.p. Super Turbo-Fire V8\*.




GLAMOR THAT KNOWS HOW TO WORK HARD, El Camino takes big cargoes; the pickup box is 761/4" long, 641/4" wide, and 123/4" deep! Side panels are double-walled to protect the smooth exterior appearance. Graintight tailgate is constructed to last, and so is the durable, steel-ribbed body floor.

\*Optional at extra cost

## **SPECIFICATIONS**

AXLE. FRONT: Independent suspension; capacity 2450 lb. AXLE. REAR: Ratio 3.55; capacity 3000 lb. BRAKES, SERVICE: Front 11" x 2%"; rear 11" x 2"; lining area 199 sq. in. BUMPERS: Front and rear. CLUTCH: (1180) dia. 9½"; (1280) dia. 10". DIRECTIONAL SIGNALS: Front and rear. ENGINE: (1180) Hi-Thrift 6; (1280) Turbo-Fire V8. FRAME: Safety-Girder. FUEL TANK: Capacity 17 gallons. GENERATOR: 12-Volt, 30-amp. LIGHTS: Head, parking, dual tail and stop; directional signals. MIRROR, REARVIEW: Interior. SHOCK ABSORBERS: Front and Rear. SPRINGS, FRONT: Coil; capacity 1030 lb. ea. at ground. SPRINGS, REAR: Coil, capacity 1315 lb. ea. at ground. STEERING: Ball-gear; ratio 28.0; wheel dia. 17". TIRES: Five tubeless 8.00-14/4PR front, single rear, spare. TRANSMISSION: 3-speed Synchro-Mesh. WHEELS: Five 14" x 5J; spare carrier inside cab. WINDSHIELD WIPERS: Dual electric; single-speed.

All illustrations and specifications contained in this literature are based on the latest product information available at the time of publication approval. The right is reserved to make changes at any time without notice in prices, colors, materials, equipment, specifications and models, and also to discontinue models. CHEVROLET MOTOR DIVISION, GENERAL MOTORS CORPORATION, DETROIT 2, MICH.



## CHEVROLET E. C. IIII

