

Mr. W. P. Steel

Studebaker Automotive Sales Corp.

P. O. Box 58445

7 Los Angeles 58, California

PSM

STUDEBAKER AUTOMOTIVE SALES CORPORATION

SUBSIDIARY OF

STUDEBAKER CORPORATION

SOUTH BEND 27, INDIANA

January 7, 1963

To Recipients of Studebaker AMA Specifications:

The attached are revised pages to the Studebaker - Special
Equipment Specifications covering Model R-3 304.5 Cu. In.
supercharged engine.

Yours truly,



H. J. Symon, Manager
Service Publications

HJS/dh

Attachment

AMA Specifications – Passenger Car

The information contained herein is prepared, distributed by, and is solely the responsibility of the automobile manufacturing company to whose products it relates. Questions concerning these specifications should be directed to the manufacturer whose address is shown below. This uniform specification form was developed by the automobile manufacturing companies under the auspices of the Automobile Manufacturers Association.

MANUFACTURER STUDEBAKER AUTOMOTIVE SALES CORPORATION	CAR NAME STUDEBAKER Special Equipment Specifications
MAILING ADDRESS 635 S. MAIN STREET SOUTH BEND 27, INDIANA	MODEL YEAR 1963 ISSUED: July 23, 1962 REVISED (•) Nov. 15, 1962

NOTES:

1. The Specifications herein are those in effect at date of compilation and are subject to change without notice by the manufacturer.
2. UNLESS OTHERWISE INDICATED:
 - a. Specifications apply to standard models without optional equipment. Significant deviations are noted.
 - b. Nominal design dimensions are used throughout these specifications.

TABLE OF CONTENTS

General Specifications 1	Drive Units 15	Rear Suspension 21	Body & Car – General 22
Engine – Mechanical 2	Brakes 18	Body Dimensions 22	Weights 33
Electrical 10	Front Suspension & Steering . . 19	Station Wagon 31	Index 37

BODY—TYPES AND STYLE NAMES—

Body type, number of passenger & style names; use manufacturer's code for series & body style.

SUPPLEMENTARY INFORMATION COVERING SPECIAL MODEL R-3, 304.5 CU. IN.
SUPERCHARGED ENGINE AND OTHER COMPONENTS AVAILABLE AS SPECIAL ORDER
OPTIONS ON LARK, HAWK, CRUISER AND AVANTI MODELS.

(SUPPLEMENTS 1963 AMA SPECIFICATIONS)

AMA Specifications—Passenger Car

Page 2

MAKE OF CAR STUDEBAKER MODEL YEAR 1963 DATE ISSUED 7-23-62 REVISED (*) 11-15-62

R-3 ENGINE

MODEL _____

ENGINE—GENERAL

Type, no. cyls., valve arr.	V8 - Valve in Head
Bore and stroke (nominal)	3-21/32 x 3-5/8
Piston displacement, c.u. in.	304.5
Bore spacing (C/L to C/L)	4.5"
No. system (front to rear)	L. Bank 1-3-5-7 R. Bank 2-4-6-8
Firing order	1-8-4-3-6-5-7-2
Compres. ratio (nominal)	9.75 Will Vary According to Tolerance
Cylinder Head Material	Cast Iron
Cylinder Block Material	Cast Iron
Cylinder Sleeve—Wet, dry, none	None
Number of mounting points	Front 2 Rear 1
Engine installation angle	5° - 49'
Taxable horsepower $\frac{\text{Dia.}^2 \times \text{No. Cyl.}}{2.5}$	42.5
Published max. bhp* @ eng. RPM	305 @ 5200 RPM and 6 lbs. Manifold Pressure
Published max. torque* (lb. ft. @ RPM)	320 @ 4000 RPM
Recommended fuel regular - premium	Premium
Idle speed (spec. neutral or drive)	Manual N.A. Automatic N.A.

ENGINE—PISTONS

Material	Aluminum - 2018T6
Description and finish	(Tru-Forged) Tin-Plated
Weight (piston only) oz.	17.60
Clearance (limits)	Top land .038 - .040 Skirt Top Selective Fit Bottom Selective Fit
Ring groove depth	No. 1 ring N.A. No. 2 ring N.A. No. 3 ring N.A. No. 4 ring

* Max. bhp (brake horsepower) and max. torque corrected as defined by SAE Engine Test Code.

1. Combustion chambers and valve port openings are hand polished and controlled.
2. Combustion chamber volumes are hand matched to each other and are 61 ± 3 cc.
3. Piston deck heights are $.023 \pm .011$.

AMA Specifications – Passenger Car

Page 3

MAKE OF CAR STUDEBAKER MODEL YEAR 1963 DATE ISSUED 7-23-62 REVISED (•) 11-15-62

POWER TEAMS

(Indicate whether standard or optional)

MODEL AVAILABILITY	ENGINE					TRANSMISSION	AXLE RATIO (Std. first)
	Displ. cu. in.	Carburetor	Compr. Ratio	BHP @ RPM	Torque @ RPM		
Optional On Larks, Cruisers, Hawk & Avanti Supercharged	304.5	One 4 Bbl.	9.75	305 @ 5200 RPM & 6 lbs Man. Press.	320 @ 4000	T-10C and T-10D 4-Speed Manual and Automatic Transmission	2.53 2.76 2.87 3.07 3.31 3.54 3.73 3.92 4.09 4.27 4.55 4.89 5.38 All Optional

AMA Specifications – Passenger Car

Page 4

MAKE OF CAR STUDEBAKER MODEL YEAR 1963 DATE ISSUED 7-23-62 REVISED (*)11-15-62

MODEL R-3 ENGINE

ENGINE—RINGS

Function (top to bottom)	No. 1, oil or comp.	Compression
	No. 2, oil or comp.	Compression
	No. 3, oil or comp.	Oil
	No. 4, oil or comp.	---
Compression	Description - material, type, coating, etc.	Top-Cast Iron Chrome Plated 2nd-Cast Iron Granoseal
	Width	.078"
	Gap	.030" Top - .030" - 2nd
Oil	Description - material, type, coating, etc.	Chrome Plated Steel Rail
	Width	.187"
	Gap	.015 to .055
Expanders		Behind Oil Ring Only

ENGINE—PISTON PINS

Material		C. D. Steel - SAE 8620
Length		3-1/16"
Diameter		.875"
Type	Locked in rod, in piston, floating, etc.	Shrink Fit In Rod
	Bushings	In rod or piston
		Material
Clearance	In piston	.0001"-.0003" - Selective Fit
	In rod	None
Direction & amount offset in piston		1/16" Toward Thrust Side

ENGINE—CONNECTING RODS

Material		Special D. F. Steel - C-1141
Weight (oz.)		23.71 oz. (Clamped In Rod)
Length (center to center)		6.625"
Bearing	Material & Type	Steel Back - Trimetal Aluminum (Steel Back - Trimetal Copper-Lead)
	Overall length	13/16"
	Clearance (limits)	.00125 - .00375
	End play	.008" - .013"

AMA Specifications – Passenger Car

Page 4

MAKE OF CAR STUDEBAKER MODEL YEAR 1963 DATE ISSUED 7-23-62 REVISED (*) 12-28-62

MODEL R-3 ENGINE

ENGINE—RINGS

Function (top to bottom)	No. 1, oil or comp.	Compression
	No. 2, oil or comp.	Compression
	No. 3, oil or comp.	Oil
	No. 4, oil or comp.	---
Compression	Description - material, type, coating, etc.	Top-Cast Iron Chrome Plated 2nd-Cast Iron Granoseal
	Width	.078"
	Gap	.030" Top - .030" - 2nd
Oil	Description - material, type, coating, etc.	Chrome Plated Steel Rail
	Width	.187"
	Gap	.015 to .055
Expanders		Behind Oil Ring Only

ENGINE—PISTON PINS

Material		C. D. Steel - SAE 8620
Length		3-1/16"
Diameter		.875"
Type	Locked in rod, in piston, floating, etc.	Shrink Fit In Rod (Clamped In Rod - Opt.)
	Bushing	In rod or piston
	Material	None
Clearance	In piston	.0001"-.0003" - Selective Fit
	In rod	None
Direction & amount offset in piston		1/16" Toward Thrust Side

ENGINE—CONNECTING RODS

Material		Special D. F. Steel - C-1141
Weight (oz.)		23.71 oz. (Clamped In Pin)
Length (center to center)		6.625"
Bearing	Material & Type	Steel Back - Trimetal Aluminum (Steel Back - Trimetal Copper-Lead)
	Overall length	13/16"
	Clearance (limits)	.00125 - .00375
	End play	.008" - .013"

AMA Specifications—Passenger Car

Page 5

MAKE OF CAR STUDEBAKER MODEL YEAR 1963 DATE ISSUED 7-23-62 REVISED 11-15-62

MODEL R-3 ENGINE

ENGINE—CRANKSHAFT

Material		D.F. Steel - SAE 1045	
Vibration damper type		Rubber Mounted Inertia Member	
End thrust taken by bearing (No.)		#1	
Crankshaft end play		.003" to .006"	
Main bearing	Material & type		Front & Rear - Steel Back Babbitt Lined #2-3 & 4 - Steel Back Trimetal Aluminum *
	Clearance		.0018 - .0043
	Journal dia. and bearing overall length	No. 1	2.500" - 1.309"
		No. 2	2.500" - .906"
		No. 3	2.500" - .906"
		No. 4	2.500" - .906"
		No. 5	2.500" - 1.546"
		No. 6	---
		No. 7	---
Dir. & amt. cyl. offset		None	
Crankpin journal diameter		1.99825" - 1.99925"	

ENGINE—CAMSHAFT

Location	Cylinder Block - Center	
Material	Alloy - Cast Iron	
Bearings	Material	Steel Back - Babbitt Lined
	Number	5
Type of Drive	Gear or chain	Gear
	Crankshaft gear or sprocket material	Cast Iron
	Camshaft gear or sprocket material	Aluminum
	Timing chain	No. of links None
		Width None
		Pitch None

ENGINE—VALVE SYSTEM

Hydraulic lifters (Std, opt, NA)	N.A.	
Valve rotator, type (intake, exhaust)	None	
Rocker ratio	1.5 to 1	
Operating tappet clearance (indicate hot or cold)	Intake	.023" - .025" Hot
		.025" - .027" Cold
	Exhaust	.023" - .025" Hot
		.025" - .027" Cold
Timing marks on flywheel, damper, other	Damper	

* Steel Back Type Trimetal Copper-Leak, Optional

(Continued)

AMA Specifications—Passenger Car

Page 6

MAKE OF CAR STUDEBAKER MODEL YEAR 1963 DATE ISSUED 7-23-62 REVISED (*)11-15-62

MODEL R-3 ENGINE

ENGINE—VALVE SYSTEM (cont.)

Timing	Intake	Opens (^o BTC)	28 ^o	Additional Camshaft Timings Optional
		Closes (^o ABC)	80 ^o	
		Duration - deg.	288 ^o	
	Exhaust	Opens (^o BBC)	80 ^o	
		Closes (^o ATC)	28 ^o	
		Duration - deg.	288 ^o	
Valve opening overlap		56 ^o		
Intake	Material		Sil. XBE - (HNV6)	
	Overall length		5-5/32"	
	Actual overall head dia.		1-7/8"	
	Angle of seat & face		45 ^o	
	Seat insert material		None	
	Stem diameter		11/32"	
	Stem to guide clearance		.0015" - .0035"	
	Lift (@ zero lash)		.400"	
	Outer spring press. and length	Valve closed (lb. @ in.)	67-75 @ 2.031"	
		Valve open (lb. @ in.)	148-160 @ 1.631"	
	Inner spring press. and length	Valve closed (lb. @ in.)	None	
		Valve open (lb. @ in.)	None	
Exhaust	Material		SAE EV8 (21-4N) - (Stellite Faced)	
	Overall length		5-5/32"	
	Actual overall head dia.		1-5/8"	
	Angle of seat & face		45 ^o	
	Seat insert material		None	
	Stem diameter		11/32"	
	Stem to guide clearance		.0015" - .0035"	
	Lift (@ zero lash)		.400"	
	Outer spring press. and length	Valve closed (lb. @ in.)	67-75 @ 2.031"	
		Valve open (lb. @ in.)	148-160 @ 1.631"	
	Inner spring press. and length	Valve closed (lb. @ in.)	None	
		Valve open (lb. @ in.)	None	

ENGINE—LUBRICATION SYSTEM

Type of lubrication (splash, pressure, nozzle)	Main bearings	Full Pressure
	Connecting rods	Full Pressure
	Piston pins	Splash
	Camshaft bearings	Full Pressure
	Tappets	Full Pressure
	Timing gear or chain	Full Pressure
	Cylinder walls	Directed Jet

(Continued)

AMA Specifications—Passenger Car

Page 6

MAKE OF CAR STUDEBAKER MODEL YEAR 1963 DATE ISSUED 7-23-62 REVISED (*)12-28-62

MODEL

R-3 ENGINE

ENGINE—VALVE SYSTEM (cont.)

Timing	Intake	Opens (^o BTC)	28 ^o	} Additional Camshaft Timings Optional
		Closes (^o ABC)	80 ^o	
		Duration - deg.	288 ^o	
	Exhaust	Opens (^o BBC)	80 ^o	
		Closes (^o ATC)	28 ^o	
		Duration - deg.	288 ^o	
Intake	Valve opening overlap		56 ^o	
	Material		Si1. XBE - (HNV6)	
	Overall length		5-5/32"	
	Actual overall head dia.		1-7/8"	
	Angle of seat & face		45 ^o	
	Seat insert material		None	
	Stem diameter		11/32"	
	Stem to guide clearance		.0015" - .0035"	
	Lift (@ zero lash)		13/32"	
	Outer spring press. and length	Valve closed (lb. @ in.)	67-83 @ 2.031"	
		Valve open (lb. @ in.)	150-172 @ 1.631"	
	Inner spring press. and length	Valve closed (lb. @ in.)	None	
		Valve open (lb. @ in.)	None	
Exhaust	Material		SAE EV8 (21-4N) - (Stellite Faced)	
	Overall length		5-5/32"	
	Actual overall head dia.		1-5/8"	
	Angle of seat & face		45 ^o	
	Seat insert material		None	
	Stem diameter		11/32"	
	Stem to guide clearance		.0015" - .0035"	
	Lift (@ zero lash)		13/32"	
	Outer spring press. and length	Valve closed (lb. @ in.)	67-83 @ 2.031"	
		Valve open (lb. @ in.)	150-172 @ 1.631"	
	Inner spring press. and length	Valve closed (lb. @ in.)	None	
		Valve open (lb. @ in.)	None	

ENGINE—LUBRICATION SYSTEM

Type of lubrication (splash, pressure, nozzle)	Main bearings	Full Pressure
	Connecting rods	Full Pressure
	Piston pins	Splash
	Camshaft bearings	Full Pressure
	Tappets	Full Pressure
	Timing gear or chain	Full Pressure
	Cylinder walls	Directed Jet

(Continued)

AMA Specifications – Passenger Car

Page 7

MAKE OF CAR STUDEBAKER MODEL YEAR 1963 DATE ISSUED 7-23-62 REVISED (a) 11-15-62

MODEL _____ R-3 ENGINE

ENGINE—LUBRICATION SYSTEM (cont.)

Oil pump type	Spur Gear
Normal oil pressure (lb. @ engine rpm)	30 @ 2000
Oil pressure sending unit (elect. or mech.)	Mechanical
Type oil intake (floating, stationary)	Stationary
Oil filter system (full flow, partial, other)	Full Flow
Filter replacement (element, complete)	Complete
Capacity of crankcase, less filter-refill (qt.)	6 Std. (7-10 Optional)
Oil grade recommended (SAE viscosity and temperature range)	+32° - SAE 40 +10° - SAE 20 -10° - SAE 10W Below -10° - SAE 5W
Engine Service Requirement (MM, MS, etc.)	MS alone or in combination with MM, ML, DG

ENGINE—EXHAUST SYSTEM

Type (single, single with cross-over, dual, other)	Dual
Muffler No. & type (reverse flow, straight thru, separate resonator)	2 - Straight Thru - Glass Wool Pack
Exhaust pipe dia. (O.D.)	Branch --- Main 2"
Exhaust pipe wall thickness	2"
Tail pipe diameter (O.D. & wall thickness)	2"

ENGINE—CRANKCASE VENTILATION SYSTEM

Type (ventilates to atmos., induction system, other)	Standard Optional	Atmosphere ---
Control unit	Make and model Location Energy source (manifold vacuum, carburetor air stream, other) Control method (variable orifice, fixed orifice, other)	None --- --- ---
Complete system	Discharges (to intake manifold, carb. air intake, air cleaner intake, other) Air inlet (breather cap, carburetor air cleaner, other) Flame arrestor (screen, check valve, other)	Atmosphere Breather Caps ---

AMA Specifications – Passenger Car

Page 7

MAKE OF CAR STUDEBAKER MODEL YEAR 1963 DATE ISSUED 7-23-62 REVISED (*)12-28-62

MODEL R-3 ENGINE

ENGINE—LUBRICATION SYSTEM (cont.) *

Oil pump type	Spur Gear
Normal oil pressure (lb. @ engine rpm)	30 @ 2000
Oil pressure sending unit (elect. or mech.)	Mechanical
Type oil intake (floating, stationary)	Stationary
Oil filter system (full flow, partial, other)	Full Flow
Filter replacement (element, complete)	Complete
Capacity of crankcase, less filter-refill (qt.)	6 Std. (7-10 Optional)
Oil grade recommended (SAE viscosity and temperature range)	+32° - SAE 40 +10° - SAE 20 -10° - SAE 10W Below -10° - SAE 5W
Engine Service Requirement (MM, MS, etc.)	MS alone or in combination with MM, ML, DG

ENGINE—EXHAUST SYSTEM

Type (single, single with cross-over, dual, other)	Dual
Muffler No. & type (reverse flow, straight thru, separate resonator)	2 - Straight Thru - Glass Wool Pack
Exhaust pipe dia. (O.D. wall thickness)	Branch --- Main 2"
Tail pipe diameter (O.D. & wall thickness)	2"

ENGINE—CRANKCASE VENTILATION SYSTEM

Type (ventilates to atmos., Induction system, other)	Standard Optional	Atmosphere ---
Control unit	Make and model Location Energy source (manifold vacuum, carburetor air stream, other) Control method (variable orifice, fixed orifice, other)	None --- --- ---
Complete system	Discharges (to Intake manifold, carb. air intake, air cleaner intake, other) Air inlet (breather cap, carburetor air cleaner, other) Flame arrestor (screen, check valve, other)	Atmosphere Breather Caps ---

* Oil Cooler - Optional

AMA Specifications— Passenger Car

Page 8

MAKE OF CAR STUDEBAKER MODEL YEAR 1963 DATE ISSUED 7-23-62 REVISED (•)11-15-62

MODEL _____ R-3 ENGINE

ENGINE—FUEL SYSTEM

(See Supplement to Page 8 for Details of Fuel Injection, Supercharger, etc. if used)

Induction type: Carburetor, fuel injection, supercharger.		Carburetor - Supercharged	
Fuel Tank	Capacity (gals.)	21 Gal. - Std. 26.5 Gal. - Optional **	
	Filler location	Left Side - Rear Quarter Panel	
Fuel Pump	Type (elec. or mech.)	Mechanical *	
	Locations	Left Front of Engine	
	Pressure range	N.A.	
Vacuum booster (std., optional, none)		None	
Fuel Filter	Type	Pleated Paper	
	Locations	In Line Between Pump & Carburetor	
Carburetor	Choke type	Automatic	
	Intake manifold heat control (exhaust or water)	Exhaust	
	Air clnr. type	Plasticized Paper	
		None	

CARBURETOR SUPPLEMENTARY INFORMATION

Model Usage	Engine Displ.	Transmission	Carburetors		No. Used and Type	Barrel Size
			Make	Model		
R3 Engine	304.5	4-Speed and Automatic	Carter	AFB	One 4 Bbl.	1-7/16 Pri. 1-11/16 Sec.

* Booster Electric Fuel Pump - Optional - Mounts Under Gas Tank

** On Avanti Only - 18 Gal. on Lark, Cruiser, and Hawk

Form Rev. 3-62

AMA Specifications – Passenger Car

Page 9

MAKE OF CAR STUDEBAKER MODEL YEAR 1963 DATE ISSUED 7-23-62 REVISED 11-15-62

MODEL _____

R-3 ENGINE

ENGINE—COOLING SYSTEM

Type system (pressure, pressure vented, atmospheric, other)			Pressure - Atmospheric Vented
Radiator cap relief valve pressure			12 - 15 P.S.I.
Circulation thermostat	Type (choke, bypass)	Choke	
	Starts to open at (°F)	170° F.	
Water pump	Type (centrifugal, other)	Centrifugal	
	GPM @ 1000 pump rpm		
	Number of pumps	1	
	Drive (V-belt, other)	V-Belt	
	Bearing type	Sealed Double Row-Ball	
By-pass recirculation type (internal, external)			Internal
Radiator core type (cellular, tube and fin, other)			Cellular - Tubular - Cross-Flow
Cooling system capacity	With heater (qt.)	18 Qts.	
	Without heater (qt.)	17 Qts.	
	Opt. equipment-specify (qt.)	None	
Water jackets full length of cylinder (yes, no)			Yes
Water all around cylinder (yes, no)			Yes
Radiator hose	Lower	Number and type (molded, straight)	One - Moulded
		Inside diameter	1-3/4"
	Upper	Number and type (molded, straight)	One - Moulded
		Inside diameter	1-3/4"
	By-pass	Number and type (molded, straight)	None
		Inside diameter	----
Fan	Number of blades & Spacing	5 Blades - (65° - 65° - 92° - 46° - 92°)	
	Diameter	14" Std. - 17" Opt.	
	Ratio-fan to crankshaft rev.	Various	
	Fan cutout type	2500 - (Viscous Drive)	
	Bearing type	Double Row - Ball	
*Drive belts (indicate belt used by letter)	Fan	D	
	Generator	D	
	Water Pump	D	
	Power Steering	B	
	Air Conditioning		
	Supercharger	E	

* Drive Belt Dimensions	B	D	E
Angle of V	38°	38°	38°
Nominal length (SAE)			
Width	15/32"	15/32"	15/32"

AMA Specifications – Passenger Car

Page 10

MAKE OF CAR STUDEBAKER MODEL YEAR 1963 DATE ISSUED 7-23-62 REVISED (*)11-15-62

MODEL

R-3 ENGINE

ELECTRICAL—SUPPLY SYSTEM

Battery	Make and Model		Willard - HDD-3EE
	Voltage Rtg. & Total Plates		12V.
	SAE Designation & Amp Hr. Rtg		60 Amp. Hr.
	Location		Under Hood - Left Fender
Alternator Generator	Terminal grounded		Negative
	Make		Electric Auto-Lite Co.
	Model		ALE-5003
	Type		DC - Diode Rectification
	Ratio—Gen. to Cr/s rev.		Various
Regulator	Gen. cut-in (hot)—engine rpm		900 Alternator RPM
	Make		Electric Auto-Lite Co.
	Model		VBV 6221A
	Type		Vibrating
	Cutout relay	Closing voltage @ generator rpm	N.A.
		Reverse current to open	None
	Regulated	Voltage	14.0-14.4 Upper Contacts
		Current	None
	Voltage test conditions	Temperature	70°
		Load	10 Amps.
		Other	20 Min. @ 2000 Alternator RPM

ELECTRICAL—STARTING SYSTEM

Starting motor	Make		Electric Auto-Lite Co.
	Model		MDU-7025
	Rotation (drive end view)		Clockwise
	Engine cranking speed		160
	Test conditions		Normal Engine Operating Temp.
	Lock test	Amps	435
		Volts	60
		Torque (lb. ft.)	11
	No load test	Amps	55
		Volts	10
		RPM (min.)	5200
Motor control	Switch (solenoid, manual)		Solenoid
	Starting procedure		1. Rotate ignition key clockwise to starting position 2. When engine starts, permit the key to return to ignition "ON" position.

(Continued)

AMA Specifications – Passenger Car

Page 11

MAKE OF CAR STUDEBAKER MODEL YEAR 1963 DATE ISSUED 7-23-62 REVISED (11-15-62)

MODEL _____

R-3 ENGINE

ELECTRICAL—STARTING SYSTEM (cont.)

Motor Drive	Engagement type		Bendix - Folo-thru
	Pinion meshes (front, rear)		Front
	Number of teeth	Pinion	9
		Flywheel	162
	Flywheel tooth face width		.375"

ELECTRICAL—IGNITION SYSTEM - Prestolite Transnigiter Model 201

Coil	Make		Prestolite
	Model		200826
	Amps	Engine stopped	10
		Engine idling	4.5 - 5.0
Distributor	Make		Electric Auto-Lite - Dual Breaker
	Model		IBB 4110
	Cent'fgal adv. in crankshaft degrees @ engine rpm (nominal)	Start (rpm)	---
		Intermediate points deg. @ rpm	---
		Max deg. @ rpm	---
	Vacuum adv. in crankshaft degrees @ in. Hg. (nominal)	Start (in Hg.)	None
		Intermediate points, deg @ in Hg	
		Max. deg. in. Hg.	
	Breaker gap (in.)		.011" - .016"
	Cam angle (deg.)		39° - 43°
Timing	Breaker arm tension (oz.)		21 - 25 oz.
	Crankshaft deg. @ rpm.		26° @ 4000 RPM
	Mark location		On Damper Flywheel
	Cylinder numbering system (see page 2)		L. Bank-1-3-5-7 R. Bank-2-4-6-8
Spark Plug	Firing order (see page 2)		1-8-4-3-6-5-7-2
	Make and model		Normal Use Champion J-9Y Champion J-61Y or J-79 - Competition
	Thread (mm)		14
	Tightening torque (lb. ft.)		24-30
Cable	Gap		.033" - .038"
	Conductor type		Stainless Steel
	Insulation type		Silicon
	Spark plug protector		Applied or Molded Terminal Cover

ELECTRICAL—SUPPRESSION

Locations & type	.5 MFD Condensers at Ignition Coil, Generator Armature and Voltage Regulator, with Radio Only.
	10,000 OHM - In Distributor Rotor - Ground at Oil Pipe.

AMA Specifications – Passenger Car

Page 12-14

MAKE OF CAR STUDEBAKER MODEL YEAR 1963 DATE ISSUED 7-23-62 REVISED (*)11-15-62
MODEL _____ R-3 ENGINE _____

**Pages 12-14 were related to
electrical bulbs and were not included
in this submission**

AMA Specifications – Passenger Car

Page 15

MAKE OF CAR STUDEBAKER MODEL YEAR 1963 DATE ISSUED 7-23-62 REVISED (*)11-15-62

MODEL _____

R-3 ENGINE COMPONENTS

DRIVE UNITS—CLUTCH (Manual Transmission)

Make & type		Borg & Beck Semi-Centrifugal
Type pressure plate springs		Coil
Effective plate pressure (lb.)		2217
No. of clutch driven discs		1
Clutch facing	Material	Woven - Molded
	Outside & inside dia.	10-1/2 x 6-1/2
	Total eff. area (sq.in.)	106.8
	Thickness	.135
	Engagement cushioning method	Plate Cushion Springs
Release bearing	Type & method of lubrication	Single Row Ball - Prelubricated
Torsional damping	Methods: springs, friction material	Coil Springs & Steel Washers

DRIVE UNITS—TRANSMISSIONS

Manual (std. or opt.)	4-Speed - Std.
Manual with overdrive (std. or opt.)	N.A.
Automatic (std. or opt.)	N.A.

DRIVE UNITS—MANUAL TRANSMISSION

Number of forward speeds		4-Speed - Warner AS6-T10D	
Transmission ratios	In first	2.54:1	
	In second	1.89:1	
	In third	1.51:1	
	In fourth	1.00:1	
	In reverse	2.61:1	
Synchronous meshing, specify gears		1st, 2nd, 3rd, 4th	
Shift lever location		Floor	
Lubricant	Capacity (pt.)		2.5
	Type recommended		Mineral Gear Lubricant
	SAE viscosity number	Summer	SAE 80
		Winter	SAE 80
		Extreme cold	SAE 80

AMA Specifications – Passenger Car

Page 15

MAKE OF CAR STUDEBAKER MODEL YEAR 1963 DATE ISSUED 7-23-62 REVISED (*) 12-28-62

MODEL R-3 ENGINE COMPONENTS

DRIVE UNITS—CLUTCH (Manual Transmission)

Make & type	Borg & Beck Semi-Centrifugal	
Type pressure plate springs	Coil	
Effective plate pressure (lb.)	2217	
No. of clutch driven discs	1	
Clutch facing	Material	Woven - Molded
	Outside & inside dia.	10-1/2 x 6-1/2
	Total eff. area (sq.in.)	106.8
	Thickness	.135
	Engagement cushioning method	Plate Cushion Springs
Release bearing	Type & method of lubrication	Single Row Ball - Prelubricated
Torsional damping	Methods: springs, friction material	Coil Springs & Steel Washers

DRIVE UNITS—TRANSMISSIONS

Manual (std. or opt.)	4-Speed T10D - Std. -- 4-Speed T10C - Opt.
Manual with overdrive (std. or opt.)	N.A.
Automatic (std. or opt.)	Optional

DRIVE UNITS—MANUAL TRANSMISSION Standard

Optional

Number of forward speeds		4-Speed - Warner AS6-T10D	Warner AS17-T10C
Transmission ratios	In first	2.54:1	2.20:1
	In second	1.89:1	1.66:1
	In third	1.51:1	1.31:1
	In fourth	1.00:1	1.00:1
	In reverse	2.61:1	2.26:1
Synchronous meshing, specify gears		1st, 2nd, 3rd, 4th	
Shift lever location		Floor	
Lubricant	Capacity (pt.)	2.5	
	Type recommended	Mineral Gear Lubricant	
	SAE viscosity number	Summer	SAE 80
		Winter	SAE 80
		Extreme cold	SAE 80

AMA Specifications – Passenger Car

Page 16

MAKE OF CAR STUDEBAKER MODEL YEAR 1963 DATE ISSUED 7-23-62 REVISED (11-15-62)

MODEL _____

R-3 ENGINE COMPONENTS

DRIVE UNITS—MANUAL TRANSMISSION WITH OVERDRIVE

For transmission data see manual transmission section

Overdrive	Type (planetary or other)		
	Manual lockout (yes, no)		
	Downshift accelerator control (yes, no)		
	Minimum cut-in speed		
	Gear ratio		
	Lubricant	Capacity (pt.) (Overdrive only)	
		Separate filler (yes, no)	
		Type recommended	
		SAE viscosity number	Summer Winter Ext. cold

DRIVE UNITS—AUTOMATIC TRANSMISSION

Trade name		Warner AS2-10
Type describe		Torque Converter and Compound Planetary
Method of Selection (Lever, Push Button or other)		Floor – Lever
Selector Pattern		P-R-N-D-2-1
List gear ratios Selector Pattern and indicate which are used in each selector position		1 – 1st gear – Torque Converter x 2.40:1 2 and D – 2nd gear – Torque Converter x 1.47:1 D – 3rd gear – Torque Converter x 1.00:1 R – Reverse – Torque Converter x 2.00:1
Max. upshift speeds—drive range		82 with 3.31 axle; 72 with 3.73 axle
Max. kickdown speeds—drive range		73 with 3.31 axle; 64 with 3.73 axle
Torque converter	Number of elements	3
	Max. ratio at stall	2.25:1 @ 2200 RPM
	Type of cooling (air, water)	Forced Air Plus Water
Lubricant	Capacity—refill (pt.)	18
	Type recommended	Type "A" Automatic Transmission Lubricant
Special transmission features		Manual selection of 1st and 2nd gear, inhibited on downshift; starts in 2nd gear with automatic upshift to 3rd in 'D'

DRIVE UNITS—PROPELLER SHAFT

Number used		
Type (exposed, torque tube)		
Outer diameter x length* x wall thickness	Manual transmission	
	Overdrive transmission	
	Automatic transmission	

*Center to center of universal joints, or to centerline of rear attachment.

(Continued)

Form Rev. 3-62

AMA Specifications – Passenger Car

Page 17

MAKE OF CAR STUDEBAKER MODEL YEAR 1963 DATE ISSUED 7-23-62 REVISED (*) 11-15-62

R-3 ENGINE COMPONENTS

MODEL _____

DRIVE UNITS—PROPELLER SHAFT (cont.)

Inter-mediate bearing	Type (plain, anti-friction)	
	Lubrication (fitting, prepack)	
Universal joints	Make	
	Number used	
	Type (ball and trunnion, cross, other)	
	Bearing	Type (plain, anti-friction)
Lubric. (fitting, prepack)		
Drive taken through (torque tube or arms, springs)		
Torque taken through (torque tube or arms, springs)		

DRIVE UNITS—REAR AXLE

Description (see instructions)		Hypoid - Semi-Floating - Model 44-1	
Limited Slip differential, type		Twin-Traction Limited Slip - Model 44-1 Opt.	
Drive Pinion Offset		1.5	
No. of differential pinions		2 - Std. Axle - 4 on Twin-Traction	
Gear ratios (Std. equip.)	Manual transmission 4-Speed	See Page Three	
	Overdrive transmission	None	
	Automatic transmission	None	
Ring gear O.D. (std. ratio)		8-1/2	
Pinion adjustment (shim, other)		Shim	
Pinion bearing adj. (shim, other)		Shim	
Wheel bearing type		Ball or Tapered Roller	
Lubricant	Capacity (pt.)	3	
	Type recommended	Hypoid Lubricant	
	SAE viscosity number	Summer	SAE 90
		Winter	SAE 90
		Extreme cold	SAE 80
		For Twin-Traction use Studebaker Special Lubricant	

REAR AXLE RATIO TOOTH COMBINATIONS

(See page 3 for axle ratio usage)

Axle ratio		
No. of teeth	Pinion	
	Ring gear	

AMA Specifications – Passenger Cars

Page 18-19

MAKE OF CAR STUDEBAKER MODEL YEAR 1963 DATE ISSUED 7-23-62 REVISED (a) 11-15-62
MODEL _____ R-3 ENGINE COMPONENTS

**Pages 18-19 were related to
Wheels, Tires & Brakes
and were not included
in this submission**

AMA Specifications – Passenger Cars

Page 20

MAKE OF CAR STUDEBAKER MODEL YEAR 1963 DATE ISSUED 7-23-62 REVISED (•) 11-15-62

MODEL R-3 ENGINE COMPONENTS

SUSPENSION FRONT (cont.)

Spring	Type	Independent Coil Springs
	Material	SAE 9260 or 5160 Steel
	Size (coil design height & I.D.; bar length x dia.)	8-7/8 x 4.1875 x 136.0 x .650
	Spring rate (lb. per in.)	280
	Rate at wheel (lb. per in.)	130 (Including Support Arm Bushings)
	Design load (lb. @ design height)	1565 @ 8-7/8
Stabilizer	Type (link, linkless, frameless)	Link
	Material & bar diameter	SAE 1065 - .750"

STEERING

Mechanical (std., opt., NA)				
Power (std., opt., NA)				
Wheel diameter				
Turning diameter	Outside front	Wall to wall (l. & r.)		
		Curb to curb (l. & r.)		
	Inside rear	Wall to wall (l. & r.)		
		Curb to curb (l. & r.)		
Outside wheel angle with inside wheel at 20°				
Mechanical	Gear	Type		
		Make		
		Ratios	Gear	
			Overall	
		No. wheel turns		
Power	Type (coaxial, linkage, etc.)			
	Make			
	Trade name			
	Gear	Type		
		Ratios	Gear	
			Overall	
			Pump driven by	
	Number wheel turns			
Linkage	Type			
	Location (front or rear of wheels, other)			
	Drag link (trans. or longit.)			
	Tie rods (one or two)			

(Continued)

AMA Specifications – Passenger Cars

Page 20

MAKE OF CAR STUDEBAKER MODEL YEAR 1963 DATE ISSUED 7-23-62 REVISED (*) 12-28-62

MODEL R-3 ENGINE COMPONENTS

SUSPENSION FRONT (cont.)

Spring	Type	Independent Coil Springs
	Material	SAE 9260 or 5160 Steel
	Size (coil design height & I.D.; bar length x dia.)	8-7/8 x 4.1875 x 134.0 x .650
	Spring rate (lb. per in.)	325
	Rate at wheel (lb. per in.)	130 (Including Support Arm Bushings)
Stabilizer	Design load (lb. @ design height)	1565 @ 8-7/8
	Type (link, linkless, frameless)	Link
	Material & bar diameter	SAE 1065 - .750"

STEERING

Mechanical (std., opt., NA)					
Power (std., opt., NA)					
Wheel diameter					
Turning diameter	Outside front	Wall to wall (l. & r.)			
		Curb to curb (l. & r.)			
	Inside rear	Wall to wall (l. & r.)			
		Curb to curb (l. & r.)			
Outside wheel angle with inside wheel at 20°					
Mechanical	Gear	Type			
		Make			
		Ratios	Gear		
		Overall			
	No. wheel turns				
Power	Type (coaxial, linkage, etc.)				
	Make				
	Trade name				
	Gear	Type			
		Ratios	Gear		
			Overall		
			Pump driven by		
	Number wheel turns				
Linkage	Type				
	Location (front or rear of wheels, other)				
	Drag link (trans. or longit.)				
	Tie rods (one or two)				

(Continued)

AMA Specifications – Passenger Car

Page 21

MAKE OF CAR STUDEBAKER MODEL YEAR 1963 DATE ISSUED 7-23-62 REVISED (•) 11-15-62

MODEL _____ R-3 ENGINE COMPONENTS

STEERING (cont)

Steering Axis	Inclination at camber (deg.)		
	Bearings (type)	Upper	
		Lower	
		Thrust	
Wheel alignment (range and preferred)	Caster (deg.)		
	Camber (deg.)		
	Toe-in (outside tread-inches)		
Steering spindle & joint type			
Wheel spindle	Diameter	Inner bearing	
		Outer bearing	
	Thread size		
	Bearing type		

SUSPENSION—REAR

Type and description			Semi-Elliptic Rear Springs - Asymmetric			
Drive and torq. taken through (see page 17)			Rear Springs and Radius Rods			
Spring	Type		Semi-Elliptic - Leaf			
	Material		SAE 5160 or 9260			
	Size (length x width, coil design height and I.D.; bar length & dia.)		51" x 2-1/2"			
	Spring rate (lb. per in.)		135			
	Rate at wheel (lb. per in.)		170			
	Design load (lb. at design height)		700 @ 2-1/2" Negative Camber			
	Mounting insulation type		Rubber Bushings			
	If leaf	No. of leaves		6		
		Inserts	Type and size	Button Type - 2.38 x .080 Hexagon		
			Material	Polyethlene with Graphite		
Shackle (comp. or tens.)		Compression				
Stabilizer	Type (link, linkless, frameless)		Link			
	Material		SAE 1065			
Track bar type			None			